

RETRANSFER
PRINTER

MATICA
TECHNOLOGIES

XID9300e





XID9300e

DESKTOP CARD PRINTING SYSTEM

Designed to last, the new XID9300e retransfer desktop printer is the perfect solution for on-the-spot issuance when it comes to heavy-duty cycles. It's designed for service bureaus offering 300 dpi high-performance card printing in addition to traditional direct-to-card personalization.

The XID9300e heavy-duty retransfer printer facilitates in-house, rigorous card issuance for government agencies, police and military, universities, aviation, port authorities and retail. It yields maximum cards throughout per printing cycle. Its unique card feeder module accommodates up to 350 cards while various encoders can be added in any combination. Additional feeder and encoder modules can be attached, so the number of accessible online cards can rise to 1,400.

The XID9300e Series is the most sophisticated retransfer card printer offering in the desktop card issuance market and part of the new Matica Desktop Modules (MDM) concept, offering a number of individual and unique hardware modules that can be combined. This new MDM concept is designed to meet demands from many applications in various market segments. The new powerful and flexible Matica Desktop Suite (MDS) middleware is developed to control and drive the XID9300e with its various devices and options.

And there's more: it is an ideal platform for maximizing throughput owing to its multi-feeder module which accommodates several types of cards in one production line. One single configuration can add up to four Feeder Encoding Modules (FEM) and multiple card handling without operator intervention.

It's a one-stop-shop thanks to its single wire IP connectivity and embedded IPSC Secure Controller so it's easy to install and operate – no integration challenges at all. The solution's own security features include various physical and electronic locks to prevent unauthorized access to cards and consumables.

TECHNICAL SPECIFICATIONS

Print method

Dye-sublimation retransfer (reverse transfer printing technology)

Print mode

Dual-sided over-the-edge retransfer printing

Print resolution

300 dpi

Print speed

Single sided YMCK: 29 sec per card

Encoding options

Magnetic ISO 3-tracks encoder, up to one unit per FEM

Chip contact and contactless dual encoder & contact station, up to one unit per FEM

- Mifare/DesFire and ISO 7816

- Open for 3rd party chip encoder integration upon request (USB port)

Card compatibility

PVC and composite PVC, PET-G, PC

ISO CR80, ISO 7810 (53,98 x 85,60 mm) (3.370" x 2.125")

Card hoppers

Feeder encoder module (FEM)

- Input hopper: 1 x 350 cards. Up to 4 FEMs (4 x 350 cards)

- Exception feeder: 1 card

- Reject tray: 10 cards

XID-INTerface module (XID - INT)

- Reject tray: 10 cards

Output hopper: 100 cards

Connectivity

Ethernet

Supported operating systems

Windows 7, Windows 10, Windows Server 2003, 2008, 2010

Software

Matica Desktop Suite

Consumables

Matica Genuine Consumables

Printer dimensions (W x H x D)

XID9300e base model (XID, XID-INT, FEM):

593 x 375 x 432 mm (23.35" x 14.77" x 17.00")

Weight

30.1 kg (66.36 lbs)

Warranty

Printer, FEM and XID-INT modules: 36 months or 100.000 prints

Printhead: Lifetime warranty using EDIsecure® materials

(other conditions apply)



Produktions- und HandelsGmbH
Obachgasse 20 - 1220 Vienna
Tel.: +43 1 250 95-0 -
info@variuscard.com

*Attention: The use of non-Matica brand ribbons could adversely affect the performance of your Matica hardware and void the products warranty.

www.maticatech.com

Data subject to change without notice. All trademarks stated are the property of their respective owners.
XID9300e_PD_2017_08_ENG_A4